AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1-11. (Canceled)
- 12. (Currently Amended) A mower according to claim 11; and A pull-behind mower for cutting ground vegetation, said mower configured to be pulled behind a vehicle and powered independently of the vehicle, said mower comprising:
 - a frame presenting a fore end and an aft end;
 - a hitch coupled to the fore end and configured to releasably couple the frame to the vehicle in a manner that permits pivoting of the frame relative to the vehicle;
 - a pair of laterally spaced wheels coupled to the aft end and adapted to rollingly support the frame on the ground;
 - a mowing deck operable to cut vegetation when positioned proximate the ground;
 - a support arm comprising a frame-side section rotatably coupled to the frame and a deck-side section rigidly coupled to the deck, said frame-side and deck-side sections being hingedly intercoupled;
 - a motor rigidly coupled to the frame and drivingly connected to the deck, so as to power the deck independently of the vehicle; and
 - a drive train for transferring power from the motor to the deck,
 - said drive train including a first rotatable drive shaft, a second rotatable drive shaft, and a Ujoint coupled between the first and second drive shafts.
 - 13. (Original) A mower according to claim 12, said support arm permitting pivoting of the deck relative to the frame on first and second distinct and intersecting pivot axes,

said U-joint being centered proximate the intersection of the first and second pivot axes.

- 14. (Currently Amended) A mower according to claim [[11]] 12, said frame-side section being rotatable relative to the frame on a first pivot axis, said frame-side and deck-side sections being hingedly intercoupled on a second pivot axes, said first and second pivot axes being substantially perpendicular to one another.
- 15. (Original) A mower according to claim 14, said first and second pivot axes intersecting one another.
- 16. (Original) A mower according to claim 15, said first pivot axis being generally upright.

17-24. (Canceled)

- 25. (Currently Amended) A mower according to claim [[24]] 27, said support arm permitting pivoting of the deck relative to the frame on the first and second distinct and intersecting pivot axes,
 said U-joint being centered proximate the intersection of the first and second pivot axes.
 - 26. (Canceled)
- 27. (Currently Amended) A mower according to claim [[26]] <u>30</u>, said first and second pivot axes intersecting one another.

28-29. (Canceled)

Application No. 10/814,009 Amendment dated January 20, 2006 Reply to Office Action of June 21, 2005

30. (Currently Amended) A mower according to claim 29, A pull-behind mower for cutting ground vegetation, said mower configured to be pulled behind a vehicle, said mower comprising:

a frame presenting a fore end and an aft end;

<u>a hitch coupled to the fore end and configured to releasably couple the frame to the vehicle</u> in a manner that permits pivoting of the frame relative to the vehicle;

a pair of laterally spaced wheels coupled to the aft end and adapted to rollingly support the frame on the ground;

a moving deck operable to cut vegetation when positioned proximate the ground;

a support arm comprising a frame-side section rotatably coupled to the frame and a deck-side section rigidly coupled to the deck, said frame-side and deck-side sections being hingedly intercoupled;

a motor for powering the deck;

a drive train for transferring power from the motor to the deck,

said drive train including a first rotatable drive shaft, a second rotatable drive shaft, and a Ujoint coupled between the first and second drive shafts,

said frame-side section being rotatable relative to the frame on a first pivot axis,

said frame-side and deck-side sections being hingedly intercoupled on a second pivot axes,

said first and second pivot axes being substantially perpendicular to one another,

said first pivot axis being generally upright; and

a mechanism operable to inhibit pivoting of the deck on the second pivot axis;

said mechanism being operable to selectively inhibit downward pivoting of the deck on the second pivot axis.

31. (Original) A mower according to claim 30, said mechanism comprising a cable coupled to the frame and the deck.

32. (Currently Amended) A mower according to claim 24, A pull-behind mower for cutting ground vegetation, said mower configured to be pulled behind a vehicle, said mower comprising:

a frame presenting a fore end and an aft end;

a hitch coupled to the fore end and configured to releasably couple the frame to the vehicle in a manner that permits pivoting of the frame relative to the vehicle;

a pair of laterally spaced wheels coupled to the aft end and adapted to rollingly support the frame on the ground;

a mowing deck operable to cut vegetation when positioned proximate the ground;

a support arm comprising a frame-side section rotatably coupled to the frame and a deck-side section rigidly coupled to the deck, said frame-side and deck-side sections being hingedly intercoupled;

a motor for powering the deck; and

a drive train for transferring power from the motor to the deck;

said drive train including a first rotatable drive shaft, a second rotatable drive shaft, and a Ujoint coupled between the first and second drive shafts,

said motor being rigidly coupled to the frame so as to power the deck independently of the vehicle.

- 33. (Original) A mower according to claim 32, said motor being a gas-powered motor.
- 34. (Currently Amended) A mower according to claim [[1]] <u>12</u>, said motor being a gas-powered motor.
- 35. (Currently Amended) A mower according to claim [[4]] 14, a mechanism operable to inhibit pivoting of the deck on the second pivot axis.

36. (Currently Amended) A mower according to claim 35, A pull-behind mower for cutting ground vegetation, said mower comprising:

a frame adapted to be coupled to a vehicle and rollingly supported on the ground; a motor rigidly coupled to the frame;

a mowing deck coupled to the frame for pivotal movement relative to the frame on first and second intersecting pivot axes;

a drive train for drivingly coupling the motor to the deck so that the motor powers the deck; said drive train including a first rotatable drive shaft, a second rotatable drive shaft, and a U-

joint coupled between the first and second drive shafts for rotation therewith,
said U-joint being centered proximate the intersection of the first and second pivot axes,
said deck being pivotable relative to the frame on the first pivot axis between a retracted
position and an extended position,

said deck being pivotable relative to the frame on the second pivot axis between an engaged position and a disengaged position,

said first and second pivot axes being at least substantially perpendicular to one another, said first pivot axis being generally upright; and

a mechanism operable to inhibit pivoting of the deck on the second pivot axis; and said mechanism being operable to selectively inhibit downward pivoting of the deck on the second pivot axis.

- 37. (Original) A mower according to claim 36, said mechanism comprising a cable coupled to the frame and the deck.
 - 38. (Canceled)
- 39. (Currently Amended) A mower according to claim [[1]] 12, said U-joint being a Hooke's joint.

Application No. 10/814,009 Amendment dated January 20, 2006 Reply to Office Action of June 21, 2005

- 40. (Canceled)
- 41. (Currently Amended) A mower according to claim [[24]] <u>30</u>, said U-joint being a Hooke's joint.